

GS VER Methodology

“Fuel switch from fossil fuels to biomass residues in boilers for heat generation”

I. SOURCE AND APPLICABILITY

Source

This methodology is based on the existing CDM Methodology AM0036 / Version 02.2: “Fuel switch from fossil fuels to biomass residues in boilers for heat generation”.

Revisions allow for the use of the project’s primary energy consumption instead of the generated heat in the calculation of the baseline CO₂ emissions from the combustion of fossil fuels, when the thermal efficiency of the baseline boiler is unknown.

AM0036 / Version 02.2 also refers to the latest approved versions of the following tools:

 [Tool for the demonstration and assessment of additionality](#)

 [Tool to determine methane emissions avoided from disposal of waste at a solid waste disposal site](#)

Selected approach from paragraph 48 of the CDM modalities and procedures

“Existing actual or historical emissions, as applicable”

Definitions

The following definitions apply for this methodology:

Biomass is non-fossilized and biodegradable organic material originating from plants, animals and microorganisms. This shall also include products, by-products, residues and waste from forestry and related industries as well as the non-fossilized and biodegradable organic fractions of industrial and municipal wastes. Biomass also includes gases and liquids recovered from the decomposition of non-fossilized and biodegradable organic material.

Biomass residues mean biomass by-products, residues and waste streams from agriculture, forestry and related industries.

Heat refers to heat that is utilized (e.g. steam or hot gases used for processes). Waste heat is not covered under the definition of Heat for the purpose of this methodology.

Efficiency of heat generation is defined as the quantity of heat generated per unit quantity of fuel fired (both expressed in terms of energy using the same units). The **average net efficiency of heat generation** refers to the efficiency of heat generation over a longer time interval that is representative for different loads and operation modes, including start-ups (e.g. one year). In case of several boilers, the average efficiency of heat generation in these boilers corresponds respectively to the heat generated by all boilers divided by the quantity of fuel fired in all boilers (both expressed in the same energy units).

Applicability

The methodology is applicable following the specific Gold Standard eligibility criteria as set out in the applicable Gold Standard rules and procedures. Whenever there is a conflict between the CDM and GS applicability criteria, GS criteria take precedence.

The methodology is applicable to project activities involving the replacement of (an) existing fossil-fired boiler(s) by new boiler(s) that fire(s) mainly or solely biomass residues (some fossil fuels may be co-fired, however in line with Gold Standard specific eligibility criteria¹).

The project activity may be based on the operation of heat generation boiler(s):

- In an agro-industrial plant generating the biomass residues, which is used in the activity; or
- In an independent plant where the biomass residues are procured from the nearby area or a market.

The methodology is applicable under the following conditions:

- The heat generated in the boiler(s) is:
 - Not used for power generation; or
 - If power is generated using the heat generated by the boilers, it is not increased as a result of the project activity, i.e.,
 - (a) The power generation capacity installed remains unchanged due to the implementation of the project activity and is maintained at the pre-project level throughout the crediting period; and
 - (b) The annual power generation during the crediting period is not more than 10% larger than the highest annual power generation in the most recent three years prior to the implementation of the project activity.
- The use of biomass residues or increasing the use of biomass residues beyond historical levels is technically not possible at the project site without a significant capital investment in:
 - The replacements of existing boilers
 - Or in a new dedicated biomass supply chain established for the purpose of the project (e.g., collecting and cleaning contaminated new sources of biomass residues that could otherwise not be used for energy purposes).
- The efficiency of the fossil fuel boiler(s) replaced by the new boiler(s) is unknown. Project proponents shall provide evidence that the replaced boilers have a significantly lower efficiency than the biomass boilers installed due to the project activity. This shall be demonstrated based on the age of the existing boiler(s), the status of the technology design (e.g. no economizers used for the recovery of condensation heat) and operation (e.g. limited control of boiler regulation), or industry surveys and/or expert's opinion at the time of validation.
- Existing boilers at the project site have not used biomass or biomass residues for heat generation during the most recent three years² prior to the implementation of the project activity;

¹ See applicable Gold Standard rules and procedures.

- No biomass types other than biomass residues, as defined above, are used in the boiler(s) during the crediting period.
- For projects that use biomass residues from a production process (e.g. production of sugar or wood panel boards), the implementation of the project shall not result in an increase of the processing capacity of raw input (e.g., sugar, rice, logs, etc.) or in other substantial changes (e.g., product change) in this process;
- The biomass residues used at the project site, i.e. site where the project activity is implemented, shall not be stored for more than one year;
- No significant energy quantities, except from transportation or mechanical treatment of the biomass residues, are required to prepare the biomass residues for fuel combustion, i.e. projects that process the biomass residues prior to combustion (e.g., esterification of waste oils) are not eligible under this methodology;
- The biomass residues are directly generated at the project site or transported to the project site by trucks;
- Biomass residues sourced outside of the project site do not involve a decrease of carbon pools, in particular dead wood, litter or soil organic carbon, on the land areas where the biomass residues are originating from. Biomass residues generated at the project site are of renewable origin, i.e. they originate from land areas where sustainable management practices are undertaken to ensure in particular that the level of carbon stocks on these land areas does not systematically decrease over time (carbon stocks may temporarily decrease due to harvesting) and any national or regional forestry, agriculture and nature conservation regulations are complied with. Furthermore, if the land areas are forests, they shall remain so. If these land areas are croplands or grasslands, they shall remain so or be reverted to forests.
- In case of project activities that involve the replacement or retrofit of existing boiler(s), all boiler(s) existing at the project site prior to the implementation of the project activity should be able to operate until the end of the crediting period without any retrofitting or replacement, i.e. the remaining technical lifetime of each existing boiler should at the start of the crediting period be larger than the duration of the crediting period (7 or 10 years as applicable). For the purpose of demonstrating this applicability condition, project participants should determine and document the typical average technical lifetime of boilers in the country and sector in a conservative manner, taking into account common practices in the sector and country. This may be done based on industry surveys, statistics, technical literature, historical replacement records of boilers in the company, etc. The age of the existing boiler(s) and the average technical lifetime of boilers in the country and sector should be documented in the PDD.

Furthermore, this methodology is only applicable if the most plausible baseline scenario(s):

² If the three most recent historical years prior to the implementation of the project activity are not representative for the situation at the project site (e.g., a drought in one year, a boiler unit or plant not operating during a certain year for technical reasons, etc), project participants may alternatively select the five most recent historical years from which one year may be excluded if deviating significantly from other years. The selection by project participants should be documented in the CDM-PDD and be applied to all relevant provisions and equations throughout this methodology in a consistent manner, including the applicability condition.

- For heat generation is either case H2 or case H5; and
- For the use of biomass residues is case B1, B2, B3, B4 and/or B5. If case B5 is the most plausible scenario, the methodology is only applicable if:
 - (a) The plant where the biomass residues would be used as feedstock in the absence of the project activity can be clearly identified throughout the crediting periods;
 - (b) The fuels used as substitutes for the biomass residues at that plant can be monitored by project participants.

The applicability conditions outlined in the latest approved version of the “Tool to determine methane emissions avoided from disposal of waste at a solid waste disposal site”, in addition to the above listed applicability conditions, apply if:

- CH₄ emissions, from the treatment of biomass residues, in the baseline are included;
- Where case B2 is identified as the most plausible baseline scenario for the use of biomass residues.

Project activities covered by the methodology are classified in the following CDM project sectoral scope categories:

Sectoral scope 01: Energy industries (Renewable-/non-renewable sources) ;
Sectoral scope 04: Manufacturing industries.

II. BASELINE METHODOLOGY

Project boundary

For the purpose of determining GHG emissions of the **project activity**, project participants shall include the following emissions sources:

- CO₂ emissions from on-site fossil fuel and electricity consumption that is attributable to the project activity. This may include fossil fuels or electricity used for on-site transportation or preparation of the biomass residues, e.g., the operation of shredders or other equipment, but shall not include fossil fuels co-fired in the boiler(s);
- CO₂ emissions from off-site transportation of biomass residues that are combusted in the boiler(s) to the project site.

For the purpose of determining the **baseline**, project participants shall include the following emission sources:

- CO₂ emissions from fossil fuel fired for heat generation in boilers that are displaced by heat generation with biomass residues.

Where the most likely baseline scenario for the use of the biomass residues is that the biomass residues would be dumped or left to decay under aerobic or anaerobic conditions (cases B1 or B2) or would be burnt in an uncontrolled manner without utilizing it for energy purposes (case B3), project participants may decide whether to include CH₄ emissions from the treatment of biomass residues in the baseline and from combustion of biomass residues in the boilers in the project boundary. Project participants shall either include CH₄ emissions for both project and baseline emissions or exclude them in both cases, and document their choice in the GS VER PDD.

The spatial extent of the project boundary encompasses:

- The boiler(s) and related equipment at the project site;
- The means for transportation of biomass residues to the project site (e.g., vehicles);
- The site where the biomass residues would have been left for decay under anaerobic conditions. This is applicable only to cases where the biomass residues would in the absence of the project activity be dumped under anaerobic conditions.

Table 2: Summary of gases and sources included in the project boundary, and justification/explanation where gases and sources are not included

	Source	Gas	Included?	Justification / Explanation	
Baseline	Fossil fuel combustion in boilers for heat generation	CO ₂	Yes		
		CH ₄	No	Excluded for simplification. This is conservative.	
		N ₂ O	No	Excluded for simplification. This is conservative.	
	Uncontrolled burning or decay of the biomass residues	CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass residues do not lead to changes of carbon pools in the LULUCF sector.	
		CH ₄	To be decided by PPs	Project participants may decide to include this emission source, where cases B1, B2 or B3 are identified as the most likely baseline scenario for the use of the biomass residues.	
			N ₂ O	No	Excluded for simplification. This is conservative.
Project Activity	On-site fossil fuel and electricity consumption	CO ₂	Yes		
		CH ₄	No	Excluded for simplification. This emission source is assumed to be very small.	
		N ₂ O	No	Excluded for simplification. This emission source is assumed to be very small.	
	Off-site transportation of biomass residues	CO ₂	Yes		
		CH ₄	No	Excluded for simplification. This emission source is assumed to be very small.	
			N ₂ O	No	Excluded for simplification. This emission source is assumed to be very small.
	Combustion of biomass residues for heat generation	CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass residues do not lead to changes of carbon pools in the LULUCF sector.	
		CH ₄	To be decided by PPs	This emission source must be included if project participants decide to include CH ₄ emissions from uncontrolled burning or decay of the biomass residues in the baseline scenario.	
			N ₂ O	No	Excluded for simplification. This emission source is assumed to be small.
	Biomass storage		CO ₂	No	It is assumed that CO ₂ emissions from surplus biomass residues do not lead to changes of carbon pools in the LULUCF sector.
			CH ₄	No	Excluded for simplification. Since biomass residues are stored for not longer than one year, this emission source is assumed to be small.
			N ₂ O	No	Excluded for simplification. This emissions source is assumed to be very small.

Procedure for the selection of the most plausible baseline scenario

For identification of the most plausible baseline scenario, project participants shall use the following step-wise procedure.

Step1: Identification of alternative scenarios to the proposed GS-VER project activity that are consistent with current laws and regulations

Identify all realistic and credible alternatives to the project activity that are consistent with current laws and regulations. Realistic and credible alternatives should be separately determined for the following two components of the project activity:

- Heat generation in the absence of the project activity;
- What would happen to the biomass residues in the absence of the project activity;

The alternatives to be analyzed for **heat generation** may include, inter alia:

- H1: The proposed project activity not undertaken as a GS-VER project activity (heat generation with biomass residues);
- H2: Continued operation of the existing boiler(s) using the same fuel mix or less biomass residues as in the past;
- H3: Continued operation of the existing boiler(s) using a different fuel (mix);
- H4: Improvement of the performance of the existing boiler(s);
- H5: Continued operation of the existing boiler(s) using the same fuel mix or less biomass residues as in the past AND installation of (a) new boiler(s) that is/are fired with the same fuel type(s) and the same fuel mix (or a lower share of biomass) as the existing boiler(s);
- H6: Replacement of the existing boiler(s) with new boiler(s)

The alternatives (including combinations) to be analyzed for **use of biomass residues** may include, inter alia:

- B1: The biomass residues are dumped or left to decay under mainly aerobic conditions. This applies, for example, to dumping and decay of biomass residues on fields;
- B2: The biomass residues are dumped or left to decay under clearly anaerobic conditions. This applies, for example, to deep landfills with more than 5 meters. This does not apply to biomass residues that are stock-piled³ or left to decay on fields;
- B3: The biomass residues are burnt in an uncontrolled manner without utilizing them for energy purposes;
- B4: The biomass residues are sold to other consumers in the market and the predominant use of the biomass residues in the region/country is for energy purposes (heat and/or power generation);
- B5: The biomass residues are used as feedstock in a process (e.g., in the pulp and paper industry);
- B6: The biomass residues are used as fertilizer;
- B7: The proposed project activity not undertaken as a GS-VER project activity (use of the biomass residues for heat generation);
- B8: Any other use of the biomass residues.

If biomass residues have already been used for heat generation at the project site prior to the implementation of the project activity, the most plausible baseline scenario for the use of the biomass

³ Further work is undertaken to investigate to which extent and in which cases methane emissions may occur from stock-piling biomass residues. Subject to further insights on this issue, the methodology may be revised.

residues should only be determined for the additional biomass residues used over and above the historical use levels.

Where different types or sources of biomass residues are used in the project activity, the most plausible baseline scenario for the use of biomass residues should be determined for each type and source of biomass separately. The respective biomass residue types, quantities and sources should be documented transparently in the GS-VER-PDD.

The alternatives to the project activity shall be in compliance with all applicable legal and regulatory requirements – taking into account EB decisions with respect to national and/or sectoral policies and regulations in determining a baseline scenario⁴ – even if these laws and regulations have objectives other than GHG reductions, e.g. to mitigate local air pollution. For example, such requirements could include a regulation on energy efficiency or emission standards for boilers.

If an alternative does not comply with all applicable legislation and regulations, then show that, based on an examination of current practice in the country or region in which the law or regulation applies, those applicable legal or regulatory requirements are systematically not enforced and that non-compliance with those requirements is widespread in the country. If this cannot be shown, then eliminate the alternative from further consideration.

Step 2: Barrier analysis to eliminate alternatives to the project activity that face prohibitive barriers

Establish a complete list of barriers that would prevent alternative scenarios for heat generation or for the use of biomass residues to occur in the absence of the GS-VER, using the guidance in Step 3 of the latest approved version of the “Tool for the demonstration and assessment of additionality”.

Since the “proposed project activity not being registered as a GS-VER project activity” shall be one of the considered alternatives, any barrier that may prevent the project activity to occur shall be included in that list. Show which alternatives for heat generation and the use of biomass residues are prevented by at least one of the barriers previously identified and eliminate those alternatives from further consideration. All alternatives shall be evaluated for a common set of barriers.

If there is only one alternative for heat generation and one scenario for the use of biomass residues that is not prevented by any barrier then these alternatives are identified as the baseline scenario. Where more than one credible and plausible alternative for heat generation or for the use of biomass residues remains, project participants shall, as a conservative assumption, use the alternative baseline scenario that results in the lowest baseline emissions as the most likely baseline scenario, or conduct an investment analysis (Step 3).

Step 3: Investment analysis (optional)

Conduct an investment analysis, consistent with the guidance in Step 2 of the latest approved version of the “Tool for the demonstration and assessment of additionality” for all combinations of alternatives for heat generation and the use of biomass residues that are remaining after the previous step. The

⁴ Annex 3 of the 22nd EB meeting report: “Clarifications on the treatment of national and/or sectoral policies and regulations (paragraph 45(e)) of the CDM Modalities and Procedures) in determining a baseline scenario (version 2)”.

economically most attractive combination of alternatives for heat generation and use of biomass residues are deemed as the most plausible baseline scenario.

Additionality

Project participants should use the latest approved version of the “Tool for the demonstration and assessment of additionality”, consistent with the guidance provided above on the selection of the most plausible baseline scenario.

Baseline emissions

Baseline emissions include CO₂ emissions from fossil fuel combustion in the boilers in the absence of the project activity and, if included in the project boundary, CH₄ emissions from the treatment of biomass residues in the absence of the project activity:

$$BE_y = BE_{HG,y} + BE_{BF,y} \tag{1}$$

Where:

- BE_y = Baseline emissions during the year y (tCO₂e/yr)
- $BE_{HG,y}$ = Baseline emissions from fossil fuel combustion for heat generation in the boiler(s) (tCO₂/yr)
- $BE_{BF,y}$ = Baseline emissions due to uncontrolled burning or decay of the biomass residues (tCO₂e/yr)

a) Baseline emissions from fossil fuel combustion in boiler(s) for heat generation (BE_{HG,y})

Baseline emissions from fossil fuel combustion in the boiler(s) are determined by multiplying the primary energy input provided by firing biomass residues in all boilers at the project site with the CO₂ emission factor of the fossil fuel type that would be used in the absence of the project activity:

$$BE_{HG,y} = EI_{PJ,biomass,y} \cdot EF_{FF,CO2} \tag{2}$$

Where:

- $BE_{HG,y}$ = Baseline emissions from fossil fuel combustion for heat generation in the boiler(s) (tCO₂e/yr)
- $EI_{PJ,biomass,y}$ = Primary energy input provided by firing biomass residues in all boilers at the project site during the year y (GJ/yr)
- $EF_{FF,CO2,y}$ = CO₂ emission factor of the fossil fuel type displaced by biomass residues (tCO_{2e} /GJ)

For the purpose of determining $EF_{FF,CO2,y}$ as a conservative approach, the least carbon intensive fuel type (i.e. the fuel type with the lowest CO₂ emission factor per GJ) should be used among the fossil types used in the heat generation equipment at the project site during the most recent three years prior to the implementation of the project activity and the fossil fuel types used in the heat generation equipment at the project site during the year y. In case of fuel additives as fire accelerant $EF_{FF,CO2,y}$ shall be addressed in a conservative manner by taking into consideration the ratio between net calorific values of the fuel and the fuel additive.

$EI_{PJ,biomass,y}$ is evaluated via two independent ways: directly via primary energy input (EI_1) and indirectly via heat generation and boiler efficiency (EI_2). Consistency is checked in the following way⁵:

$$EI_{PJ,biomass,y} = \begin{cases} (EI_1 + EI_2) / 2, & \text{if } \Delta EI < \varepsilon_1 + \varepsilon_2 \\ \min(EI_1, EI_2), & \text{otherwise} \end{cases} \quad (3)$$

Where:

- $EI_{PJ,biomass,y}$ = Primary energy input provided by firing biomass residues in all boilers at the project site during the year y (GJ/yr)
- EI_1 = Primary energy input provided directly via primary energy input at the project site during one year (GJ/yr)
- EI_2 = Primary energy input provided indirectly via heat generation and boiler efficiency at the project site during one year (GJ/yr)
- $\varepsilon_1, \varepsilon_2$ = Expected measuring errors of monitoring EI_1 and EI_2 in the year y (GJ/yr)

Method 1 (direct via primary energy input)

EI_1 is determined based on the biomass residues that are used for heat generation in the boiler(s), taking into account all biomass residue types k fired in the project boilers during a year y, as follows:

$$EI_1 = \sum_k BF_{k,y} \cdot NCV_k \quad (4)$$

Method 2 (indirect via heat generation)

EI_2 is determined based on the heat generated by the boiler(s) and their efficiencies less the energy input by fossil fuel types i fired in the project boilers during a year y, as follows:

⁵ The efficiency $\eta_{boiler,FF}$ of the replaced fossil fuel boiler is unknown. As stated in the applicability criteria replaced boilers must have a significantly lower efficiency than the newly installed biomass boiler(s):

With $\eta_{boiler,BF} \geq \eta_{boiler,FF}$

it follows:

$$HC_{PJ,biomass,y} = \frac{HG_{PJ,total,y}}{\eta_{boiler,BF}} \leq \frac{HG_{PJ,total,y}}{\eta_{boiler,FF}} \quad (2.1)$$

Therefore, the substitution of $HG/\eta_{boiler,FF}$ with EI is conservative.

- $HC_{PJ,biomass,y}$ = Primary energy provided with incremental biomass residues used as a result of the project activity during the year y (GJ/yr)
- $HG_{PJ,total,y}$ = Total heat generated in boilers at the project site, using both biomass residues and fossil fuels, during the year y (GJ/yr)
- $\eta_{boiler,FF}$ = Average net efficiency of heat generation in the boiler(s) when fired with fossil fuels
- $\eta_{boiler,BF}$ = Net efficiency of heat generation in the boiler(s) when fired with biomass residues

$$EI_2 = \frac{HG_{PJ,total,y}}{\eta_{boiler,BF}} - \sum_i FC_{i,y} \cdot NCV_i \quad (4.1)$$

Where:

EI_2	= Primary energy input provided indirectly via heat generation and boiler efficiency at the project site during one year (GJ/yr)
$HG_{PJ,total,y}$	= Total heat generated in boilers at the project site, using both biomass residues and fossil fuels, during the year y (GJ/yr)
NCV_k	= Net calorific value of the biomass residue type k (GJ/ton)
$FC_{i,y}$	= Quantity of fossil fuel type i fired in all boiler(s) at the project site during the year y (mass or volume unit) ⁶
NCV_i	= Net calorific value of the fossil fuel type i (GJ/mass or volume unit)
$\eta_{boiler,BF}$	= Net efficiency of heat generation in the boiler(s) when fired with biomass residues

b) Baseline emissions due to uncontrolled burning or decay of the biomass residues

If included in the project boundary, baseline emissions due to uncontrolled burning or decay of the biomass residues ($BE_{BF,y}$) should be determined consistent with the most plausible baseline scenario for the use of the biomass residues, following the procedures for the respective baseline scenario, as outlined below. Where different baseline scenarios apply to different types or quantities of biomass residues, the procedures as outlined below should be applied respectively to the different quantities and types of biomass residues.

Where for a certain biomass type k leakage can not be ruled out, using one of the approaches L₁, or L₂, or L₃ or L₄ outlined in the leakage section, no baseline methane emissions can be claimed from decay, dumping or uncontrolled burning of that quantity of biomass.

As no biomass has been used for heat generation at the project site during the most recent three years prior to the implementation of the project activity and the most plausible baseline scenario is that heat would continue to be generated only with fossil fuels, use $BF_{PJ,k,y} = BF_{k,y}$ for all biomass residue types k .

Uncontrolled burning or aerobic decay of the biomass residues (cases B1 and B3)

If the most likely baseline scenario for the use of the biomass residues is either that the biomass residues would be dumped or left to decay under mainly aerobic conditions (B1) or burnt in an uncontrolled manner without utilizing them for energy purposes (B3), baseline emissions are calculated assuming, for both scenarios viz., natural decay and uncontrolled burning, that the biomass residues would be burnt in an uncontrolled manner.

Baseline emissions are calculated by multiplying the quantity of biomass residues that would not be used in the absence of the project activity with the net calorific value and an appropriate emission factor, as follows:

$$BE_{BF,y} = GWP_{CH4} \cdot \sum_k BF_{PJ,k,y} \cdot NCV_k \cdot EF_{burning,CH4,k,y} \quad (4.2)$$

⁶ Preferably use a mass unit for solid fuels and a volume unit for liquid and gaseous fuels.

Where:

- $BE_{BF,y}$ = Baseline emissions due to uncontrolled burning or decay of the biomass residues (tCO₂e/yr)
- GWP_{CH_4} = Global Warming Potential of methane valid for the commitment period (tCO₂e/tCH₄)
- $BF_{PJ,k,y}$ = Quantity of biomass residue type k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter)
- NCV_k = Net calorific value of the biomass residue type k (GJ/ton of dry matter or GJ/liter)
- $EF_{burning,CH_4,k,y}$ = CH₄ emission factor for uncontrolled burning of the biomass residue type k during the year y (tCH₄/GJ)
- k = Types of biomass residues for which the identified baseline scenario is B1 or B3 and for which leakage effects could be ruled out with one of the approaches L₁, L₂ L₃ or L₄ described in the leakage section

To determine the CH₄ emission factor, project participants may undertake measurements or use referenced default values. In the absence of more accurate information, it is recommended to use 0.0027 t CH₄ per ton of biomass as default value for the product of NCV_k and $EF_{burning,CH_4,k,y}$.⁷

The uncertainty of the CH₄ emission factor is in many cases relatively high. In order to reflect this and for the purpose of providing conservative estimates of emission reductions, a conservativeness factor must be applied to the CH₄ emission factor. The level of the conservativeness factor depends on the uncertainty range of the estimate for the CH₄ emission factor. Appropriate conservativeness factors from Table 3 below shall be chosen and multiplied with the estimate for the CH₄ emission factor. For example, if the default CH₄ emission factor of 0.0027 t CH₄/t biomass is used, the uncertainty can be deemed to be greater than 100%, resulting in a conservativeness factor of 0.73. Thus, in this case an emission factor of 0.001971 t CH₄/t biomass should be used.

Table 3: Conservativeness factors

Estimated uncertainty range (%)	Assigned uncertainty band (%)	Conservativeness factor where lower values are more conservative
Less than or equal to 10	7	0.98
Greater than 10 and less than or equal to 30	20	0.94
Greater than 30 and less than or equal to 50	40	0.89
Greater than 50 and less than or equal to 100	75	0.82
Greater than 100	150	0.73

Anaerobic decay of the biomass residues (case B2)

If the most likely baseline scenario for the use of the biomass residues is that the biomass residues would decay under clearly anaerobic conditions (case B2), project participants shall calculate baseline emissions using the latest approved version of the “Tool to determine methane emissions avoided from disposal of waste at a solid waste disposal site”. The variable $BE_{CH_4,SWDS,y}$ calculated by the tool corresponds to $BE_{BF,y}$ in this methodology. Use as waste quantities prevented from disposal ($W_{j,x}$) in the tool those quantities of biomass residues ($BF_{PJ,k,y}$) for which B2 has been identified as the most plausible baseline scenario and for which leakage could be ruled out using one of the approaches L₁, L₂ L₃ or L₄ described in the leakage section.

⁷ 2006 IPCC Guidelines, Volume 4, Table 2.5, default value for agricultural residues.

Use for energy or feedstock purposes (cases B4 or B5)

The biomass residues would not decay or be burnt in an uncontrolled manner and $BE_{BF,y} = 0$.

Project emissions

Project emissions include CO₂ emissions from on-site fossil fuel and electricity consumption that is attributable to the project activity, CO₂ emissions from off-site transportation of biomass residues that are combusted in the boiler(s) to the project site, and, if included in the project boundary, CH₄ emissions from combustion of biomass residues for heat generation.

$$PE_y = PE_{CO_2,FF,y} + PE_{CO_2,EC,y} + PE_{CO_2,TR,y} + GWP_{CH_4} \cdot PE_{CH_4,BF,y} \quad (5)$$

When CO₂ emissions from on-site fossil fuel and electricity consumption attributable to the project activity ($PE_{CO_2,FF,y}$ and $PE_{CO_2,EC,y}$) and CO₂ emissions from transportation of biomass residues that are combusted in the boiler(s) ($PE_{CO_2,TR,y}$) are shown to be less than 1% each (on-site fossil fuel, electricity, transport) of the baseline GHG emissions, PE_y shall be evaluated making use of a conservative default project emission factor as follows:

$$PE_{CO_2,FF,y} + PE_{CO_2,EC,y} + PE_{CO_2,TR,y} < CF \cdot ER_y$$

$$PE_y = GWP_{CH_4} \cdot PE_{CH_4,BF,y} + CF \cdot ER_y \quad (6)$$

Where:

- PE_y = Project emissions during the year y (tCO₂/yr)
- $PE_{CO_2,FF,y}$ = CO₂ emissions from on-site fossil fuel combustion attributable to the project activity (tCO₂/yr)
- $PE_{CO_2,EC,y}$ = CO₂ emissions from on-site electricity consumption attributable to the project activity (tCO₂/yr)
- $PE_{CO_2,TR,y}$ = CO₂ emissions from off-site transportation of biomass residues to the project site (tCO₂/yr)
- GWP_{CH_4} = Global Warming Potential of methane valid for the commitment period (tCO₂e/tCH₄)
- $PE_{CH_4,BF,y}$ = CH₄ emissions from combustion of biomass residues in the boiler(s) (tCH₄/yr)
- CF = Conservative default project emission factor
- ER_y = Emission reduction (tCO₂) in year y

When CO₂ emissions from on-site fossil fuel and electricity consumption attributable to the project activity ($PE_{CO_2,FF,y}$ and $PE_{CO_2,EC,y}$) and CO₂ emissions from transportation of biomass residues that are combusted in the boiler(s) ($PE_{CO_2,TR,y}$) are shown to be more than 1 % each (on-site fossil fuel, electricity, transport) of the baseline GHG emissions, PE_y shall be monitored.

a) CO₂ emissions from on-site fossil fuel combustion ($PE_{CO_2,FF,y}$)

CO₂ emissions from on-site fossil fuel combustion that is attributable to the project activity ($PE_{CO_2,FF,y}$) are calculated by multiplying the fossil fuels consumption with appropriate net calorific values and CO₂ emission factors, as follows:

$$PE_{CO_2,FF,y} = \sum_i FC_{on-site,i,y} \cdot NCV_i \cdot EF_{CO_2,FF,i} \quad (7)$$

Where:

- $PE_{CO_2,FF,y}$ = CO₂ emissions from on-site fossil fuel combustion attributable to the project activity (tCO₂/yr)
- $FC_{on-site,i,y}$ = Quantity of fossil fuel type i combusted at the project site for purposes other than heat generation as a result of the project activity during the year y (mass or volume unit)
- NCV_i = Net calorific value of the fossil fuel type i (GJ / mass or volume unit)
- $EF_{CO_2,FF,i}$ = CO₂ emission factor for fossil fuel type i (tCO₂/GJ)

$FC_{on-site,i,y}$ should not include fossil fuels co-fired in the boiler(s) but should include all other fossil fuel consumption at the project site that is attributable to the project activity, such as for on-site transportation or treatment of the biomass residues.

b) CO₂ emissions from on-site electricity consumption ($PE_{CO_2,EC,y}$)

CO₂ emissions from on-site electricity consumption ($PE_{CO_2,EC,y}$) are calculated by multiplying the electricity consumption by an appropriate grid emission factor, as follows:

$$PE_{CO_2,EC,y} = EC_{PJ,y} \cdot EF_{grid,y} \quad (8)$$

Where:

- $PE_{CO_2,EC,y}$ = CO₂ emissions from on-site electricity consumption attributable to the project activity (tCO₂/yr)
- $EC_{PJ,y}$ = On-site electricity consumption attributable to the project activity during the year y (MWh)
- $EF_{grid,y}$ = CO₂ emission factor for electricity used from the grid (tCO₂/MWh). Use ACM0002 to calculate the grid emission factor. If electricity consumption ($EC_{PJ,y}$) is less than 15 GWh/yr, the average grid emission factor (including all grid-connected power plants) may be used

c) CO₂ emissions from transportation of biomass residues to the project site ($PE_{TR,CO_2,y}$)

In cases where the biomass residues are not generated directly at the project site, project participants shall determine CO₂ emissions resulting from transportation of the biomass residues to the project plant. In many cases transportation is undertaken by vehicles.

Project participants may choose between two different approaches to determine emissions: an approach based on distance and vehicle type (Option 1) or on fuel consumption (Option 2).

Option 1:

Emissions are calculated on the basis of distance and the number of trips (or the average truck load):

$$PE_{CO_2,TR,y} = N_y \cdot AVD_y \cdot EF_{km,CO_2} \quad (9)$$

or

$$PE_{CO_2,TR,y} = \frac{\sum_k BF_{PJ,k,y}}{TL_y} \cdot AVD_y \cdot EF_{km,CO_2,y} \quad (10)$$

Where:

- $PE_{CO_2,TR,y}$ = CO₂ emissions from off-site transportation of biomass residues to the project site (tCO₂/yr)
- N_y = Number of truck trips during the year y
- AVD_y = Average round trip distance (from and to) between the biomass fuel supply sites and the site of the project plant during the year y (km)
- $EF_{km,CO_2,y}$ = Average CO₂ emission factor for the trucks measured during the year y (tCO₂/km)
- $BF_{PJ,k,y}$ = Quantity of biomass residue type k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter)
- TL_y = Average truck load of the trucks used (tons or liter)

Option 2:

Emissions are calculated based on the actual quantity of fossil fuels consumed for transportation.

$$PE_{CO_2,TR,y} = \sum_i FC_{TR,i,y} \cdot NCV_i \cdot EF_{CO_2,FF,i} \quad (11)$$

Where:

- $PE_{CO_2,TR,y}$ = CO₂ emissions from off-site transportation of biomass residues to the project site (tCO₂/yr)
- $FC_{TR,i,y}$ = Fuel consumption of fuel type i in trucks for transportation of biomass residues during the year y (mass or volume unit)
- NCV_i = Net calorific value of the fossil fuel type i (GJ / mass or volume unit)
- $EF_{CO_2,FF,i}$ = CO₂ emission factor for fossil fuel type i (tCO₂/GJ)

d) CH₄ emissions from combustion of biomass residues in the boiler(s) ($PE_{CH_4,BF,y}$)

If this source has been included in the project boundary, emissions are calculated as follows:

$$PE_{CH_4,BF,y} = EF_{CH_4,BF} \cdot \sum_k BF_{PJ,k,y} \cdot NCV_k \quad (12)$$

Where:

- $PE_{CH_4,BF,y}$ = CH₄ emissions from combustion of biomass residues in the boiler(s) (tCH₄/yr)
- $EF_{CH_4,BF}$ = CH₄ emission factor for the combustion of the biomass residues in the boilers (tCH₄/GJ)
- $BF_{PJ,k,y}$ = Quantity of biomass residue type k used for heat generation as a result of the project activity during the year y (tons of dry matter or liter)
- NCV_k = Net calorific value of the biomass residue type k (GJ/ton of dry matter or GJ/liter)

To determine the CH₄ emission factor, project participants may conduct measurements at the plant site or use IPCC default values, as provided in Table 4 below. The uncertainty of the CH₄ emission factor is in many cases relatively high. In order to reflect this and for the purpose of providing conservative estimates of emission reductions, a conservativeness factor must be applied to the CH₄ emission factor. The level of the conservativeness factor depends on the uncertainty range of the estimate for the CH₄ emission factor. Appropriate conservativeness factor from Table 5 below shall be chosen to multiply with the estimate for the CH₄ emission factor.

For example, where the default CH₄ emission factor of 30 kg/TJ from Table 2 below is used, the uncertainty is estimated to be 300%, resulting in a conservativeness factor of 1.37. Thus, in this case a CH₄ emission factor of 41.1 kg/TJ should be used.

Table 4: Default CH₄ emission factors for combustion of biomass residues⁸

	Default emission factor (kg CH ₄ / TJ)	Assumed uncertainty
Wood waste	30	300%
Sulphite lyes (Black Liquor)	3	300%
Other solid biomass residues	30	300%
Liquid biomass residues	3	300%

Table 5: Conservativeness factors

Estimated uncertainty range (%)	Assigned uncertainty band (%)	Conservativeness factor where higher values are more conservative
Less than or equal to 10	7	1.02
Greater than 10 and less than or equal to 30	20	1.06
Greater than 30 and less than or equal to 50	40	1.12
Greater than 50 and less than or equal to 100	75	1.21
Greater than 100	150	1.37

Leakage

The main potential source of leakage for this project activity is an increase in emissions from fossil fuel combustion or other sources due to diversion of biomass residues from other uses to the project plant as a result of the project activity. Changes in carbon stocks in the LULUCF sector are expected to be insignificant since this methodology is limited to biomass residues, as defined in the applicability conditions above.

Project participants shall demonstrate that the use of the biomass residues does not result in increased use of fossil fuels or other GHG emissions elsewhere. For this purpose, project participants shall assess as part of the monitoring the supply situation for each types of biomass residue k used in the project plant. Table 6 below outlines the options that may be used to demonstrate that the biomass residues used in the plant did not increase fossil fuel consumption or other GHG emissions elsewhere.

Which approach should be used depends on the most plausible baseline scenario for the use of the biomass residues. Where scenarios B1, B2 or B3 apply, use approaches L₁, L₂ or L₃. Where scenario B4 applies, use approaches L₂ or L₃. Where scenario B5 applies, use approach L₄.

⁸ Values are based on the 2006 IPCC Guidelines, Volume 2, Chapter 2, Tables 2.2 to 2.6.

Table 6: Approaches to rule out leakage

L ₁	Demonstrate that at the sites where the project activity is supplied from with biomass residues, the biomass residues have not been collected or utilized (e.g., as fuel, fertilizer or feedstock) but have been dumped and left to decay, land-filled or burnt without energy generation (e.g. field burning) prior to the implementation of the project activity. Demonstrate that this practice would continue in the absence of the GS-VER project activity, e.g., by showing that in the monitored period no market has emerged for the biomass residues considered or by showing that it would still not be feasible to utilize the biomass residues for any purposes (e.g., due to the remote location where the biomass residue is generated).
L ₂	Demonstrate that there is an abundant surplus biomass residue of the in the region of the project activity which is not utilized. For this purpose, demonstrate that the quantity of available biomass residues of type k in the region is at least 25% larger than the quantity of biomass residues of type k that are utilized (e.g., for energy generation or as feedstock), including the project plant.
L ₃	Demonstrate that suppliers of the type of biomass residue in the region of the project activity are not able to sell all of their biomass residues. For this purpose, project participants shall demonstrate that the ultimate supplier of the biomass residue (who supplies the project) and a representative sample of suppliers of the same type of biomass residue in the region had a surplus of biomass residues (e.g., at the end of the period during which biomass residues are sold), which they could not sell and which are not utilized.
L ₄	Identify the consumer that would use the biomass residue in the absence of the project activity (e.g., the former consumer). Demonstrate that this consumer has substituted the biomass residue diverted to the project with other types of biomass residues (and not with fossil fuels or other types of biomass than biomass residues) ⁹ by showing that the former user only fires biomass residues for which leakage can be ruled out using approaches L ₂ or L ₃ . Provide credible evidence and document the types and amounts of biomass residues used by the former user as replacement for the biomass residue fired in the project activity and apply approaches L ₂ or L ₃ to these types of biomass residues. Demonstrate that the substitution of the biomass residues used in the project activity with other types of biomass residues does not require a significant additional energy input except for the transportation of the biomass residues.

Where project participants wish to use approaches L₂, L₃ or L₄ to assess leakage effects, they shall clearly define the geographical boundary of the region and document it in the GS-VER-PDD. In defining the geographical boundary of the region, project participants should take the usual distances for biomass residue transports into account, i.e., if biomass residues are transported up to 50 km, the region may cover a radius of 50 km around the project activity. In any case, the region should cover a radius around the project activity of at least 20 km but not more than 200 km. Once defined, the region should not be changed during the crediting period(s).

Project participants shall apply a leakage penalty to the quantity of biomass residues, for which project participants cannot demonstrate with one of the approaches above that the use of the biomass residue does not result in leakage. The leakage penalty aims at adjusting emission reductions for leakage effects in a conservative manner, assuming that this quantity of biomass residues is substituted by the most carbon intensive fuel in the country.

If for a certain biomass residue type k used in the project leakage effects cannot be ruled out with one of the approaches above, leakage effects for the year y shall be calculated as follows:

⁹ The generation of other types of biomass than biomass residues may be involved with significant GHG emissions, for example, from cultivation or harvesting.

$$LE_y = EF_{CO_2,LE} \cdot \sum_n BF_{LE,n,y} \cdot NCV_n \quad (13)$$

Where:

- LE_y = Leakage emissions during the year y (tCO₂/yr)
- $EF_{CO_2,LE}$ = CO₂ emission factor of the most carbon intensive fuel used in the country (tCO₂/GJ)
- $BF_{LE,n,y}$ = Quantity of biomass residue type n used for heat generation as a result of the project activity during the year y and for which leakage can not be ruled out using one of the approaches L₁, L₂, L₃ or L₄ (tons of dry matter or liter)
- NCV_n = Net calorific value of the biomass residue type n (GJ/ton of dry matter or GJ/liter)
- n = Biomass residue type n for which leakage can not be ruled out using one of the approaches L₁, L₂, L₃ or L₄

In case of approaches L₁, $BF_{LE,n,y}$ corresponds to the quantity of biomass residue type n that is obtained from the relevant source or sources.

In case of approaches L₂ or L₃, $BF_{LE,n,y}$ corresponds to the quantity of biomass residue type k used for heat generation as a result of the project activity during the year y ($BF_{LE,n,y} = BF_{PJ,k,y}$, where $n=k$).

In case of approach L₄, ($BF_{LE,n,y} \cdot NCV_n$) corresponds to the lower value of:

- (a) The quantity of fuel types m, expressed in energy quantities, that are used by the former user of the biomass residue type k and for which leakage can not be ruled out because the fuels used are either (i) fuels types other than biomass residues (e.g., fossil fuels or biomass types other than biomass residues) or (ii) are biomass residues but leakage can not be ruled out for those types of biomass residues with approaches L₂ or L₃; as follows:

$$BF_{LE,n,y} \cdot NCV_n = \sum_m FC_{former\ user,m,y} \cdot NCV_m \quad (14)$$

Where:

- $BF_{LE,n,y}$ = Quantity of biomass residue type n used for heat generation as a result of the project activity during the year y and for which leakage can not be ruled out using approach L₄ (tons of dry matter or liter)
- NCV_n = Net calorific value of the biomass residue type n (GJ/ton of dry matter or GJ/liter)
- n = Biomass residue type n for which leakage can not be ruled out using approach L₄
- $FC_{former\ user,m,y}$ = Quantity of fuel type m used by the former user of the biomass residue type n during the year y (mass or volume unit).
- NCV_m = Net calorific value of fuel type m (GJ/ton of dry matter or GJ/liter)
- m = Fuel type m, being either (i) a fuel type other than a biomass residue (e.g. fossil fuel or biomass other than biomass residues) or (ii) a biomass residues for which leakage can not be ruled out with approaches L₂ or L₃

- (b) The quantity of biomass residue type k , expressed in energy quantities, used for heat generation as a result of the project activity during the year y ($BF_{LE,n,y} = BF_{PJ,k,y}$, where $n=k$).

Emission reductions

Emission reductions are calculated as follows:

$$ER_y = BE_y - PE_y - LE_y \quad (15)$$

Where:

- ER_y = Emission reductions during the year y (tCO₂/yr)
 BE_y = Baseline emissions during the year y (tCO₂/yr)
 PE_y = Project emissions during the year y (tCO₂/yr)
 LE_y = Leakage emissions during the year y (tCO₂/yr)

In the case that negative overall emission reductions arise in a year through application of the leakage penalty, GS VERs are not issued to project participants for the year concerned and in subsequent years, until emission reductions from subsequent years have compensated the quantity of negative emission reductions from the year concerned. (For example: if negative emission reductions of 30 tCO₂e occur in the year t and positive emission reductions of 100 tCO₂e occur in the year $t+1$, only 70 GS VERs are issued for the year $t+1$.)

Data and parameters not monitored

Data / Parameter:	$EF_{CO_2,FF,i}$
Data unit:	tCO ₂ /GJ
Description:	CO ₂ emission factor for fossil fuel type i
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default emission factors (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the value in a conservative manner and justify the choice
Measurement procedures (if any):	
Any comment:	

Data / Parameter:	-
Data unit:	MWh
Description:	Highest historical electricity generation at the project site during the most recent three years prior to the implementation of the project activity
Source of data:	On-site measurements
Measurement procedures (if any):	
Any comment:	Required to assess the applicability condition referring to power generation at the project site

Data / Parameter:	CF
Data unit:	0.03
Description:	Conservative default project emission factor
Source of data:	Default value
Measurement procedures (if any):	
Any comment:	Only applicable if CO ₂ emissions from on-site fossil fuel and electricity consumption attributable to the project activity ($PE_{CO_2,FF,y}$ and $PE_{CO_2,EC,y}$) and CO ₂ emissions from transportation of biomass residues that are combusted in the boiler(s) ($PE_{CO_2,TR,y}$) are shown to be less than 1% each (on-site fossil fuel consumption, electricity, transportation) of the baseline GHG emissions.

III. MONITORING METHODOLOGY

Monitoring procedures

Describe and specify in the GS-VER-PDD all monitoring procedures, including the type of measurement instrumentation used, the responsibilities for monitoring and QA/QC procedures that will be applied. Where the methodology provides different options (e.g. use of default values or on-site measurements), specify which option will be used. All meters and instruments should be calibrated regularly as per industry practices.

Data and parameters monitored

Data / Parameter:	$\eta_{\text{boiler,BF}}$
Data unit:	-
Description:	Average net efficiency of heat generation in the boiler(s) when fired with biomass residuals
Source of data:	On-site measurement of the boiler efficiency during a representative time period.
Measurement procedures (if any):	Use recognized standards for the measurement of the boiler efficiency, such as the “British Standard Methods for Assessing the thermal performance of boilers for steam, hot water and high temperature heat transfer fluids” (BS845). Where possible, use preferably the direct method (dividing the net heat generation by the energy content of the fuels fired during a representative time period), as it is better able to reflect average efficiencies during a representative time period compared to the indirect method (determination of fuel supply or heat generation and estimation of the losses). Document measurement procedures and results and manufacturer’s information transparently in the GS-VER-PDD
Any comment:	Due to alternating operating conditions the average efficiency of the boiler may vary from one year to another. To ensure best practice in boiler operation the average efficiency shall be equal or above the manufacturer information efficiency. In case of measurement of a lower annual average $\eta_{\text{boiler,BF}}$ the manufacturer information shall be applied for the respective year.

Data / Parameter:	$EF_{FF,CO_2,y}$
Data unit:	tCO ₂ e/GJ
Description:	CO ₂ emission factor of the fossil fuel type displaced by biomass residues for the year y
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default emission factors (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the value in a conservative manner and justify the choice.
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement In case of other data sources: Review the appropriateness of the data annually.
QA/QC procedures:	Check consistency of measurements and local/national data with default values by the IPCC. If the values differ significantly from IPCC default values, collect additional information or conduct additional measurements
Any comment:	For the purpose of determining $EF_{FF,CO_2,y}$, as a conservative approach, the least carbon intensive fuel type (i.e. the fuel type with the lowest CO ₂ emission factor per GJ) should be used among the fossil types used at the project site during the most recent three years prior to the implementation of the project activity and the fossil fuel types used in the heat generation equipment at the project site during the year y. In case the old boiler is still under operation with a reduced load factor the used fuel type shall be addressed in a conservative manner.

Data / Parameter:	$HG_{PJ,total,y}$
Data unit:	GJ/yr
Description:	Total heat generated in all boilers at the project site, firing both biomass residues and fossil fuels, during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	Heat generation is determined as the difference of the enthalpy of the steam or hot water generated by the boiler(s) minus the enthalpy of the feed-water, the boiler blow-down and any condensate return. The respective enthalpies should be determined based on the mass (or volume) flows, the temperatures and, in case of superheated steam, the pressure. Steam tables or appropriate thermodynamic equations may be used to calculate the enthalpy as a function of temperature and pressure
Monitoring frequency:	Continuously, aggregated annually
QA/QC procedures:	The consistency of metered net heat generation should be cross-checked with the quantity of biomass and/or fossil fuels fired (e.g. check whether the net heat generation divided by the quantity of fuel fired results in a reasonable thermal efficiency that is comparable to previous years)
Any comment:	

Data / Parameter:	$BF_{k,y}$
Data unit:	Tons of dry matter or volume (m3)
Description:	Quantity of biomass residue type k fired in all boiler(s) at the project site during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	Use weight or volume meters. Adjust for the moisture content in order to determine the quantity of dry biomass. The quantity shall be crosschecked with the quantity of heat generated and any fuel purchase receipts (if available)
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Crosscheck the measurements with an annual energy balance that is based on purchased quantities and stock changes
Any comment:	The quantity of biomass combusted should be collected separately for all types of biomass

Data / Parameter:	Moisture content of the biomass residues
Data unit:	% Water content
Description:	Moisture content of each biomass residue type k
Source of data:	On-site measurements
Measurement procedures (if any):	
Monitoring frequency:	Continuously, mean values calculated at least annually
QA/QC procedures:	
Any comment:	In case of dry biomass, monitoring of this parameter is not necessary

Data / Parameter:	$FC_{i,y}$
Data unit:	Mass or volume unit
Description:	Quantity of fossil fuel type i fired in all boiler(s) at the project site during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Cross-check the measurements with an annual energy balance that is based on purchased quantities and stock changes
Any comment:	The quantity of fossil fuels combusted should be collected separately for all types of fossil fuels

Data / Parameter:	$FC_{on-site,i,y}$
Data unit:	Mass or volume unit
Description:	Quantity of fossil fuel type i combusted at the project site for other purposes than heat generation as a result of project activity during the year y
Source of data:	On-site measurements or purchase receipts
Measurement procedures (if any):	Use weight or volume meters. The quantity shall be cross-checked with the quantity of heat generated and any fuel purchase receipts (if available)
Monitoring frequency:	At least annually
QA/QC procedures:	
Any comment:	Shall only be monitored if default CF is not applicable. $FC_{on-site,i,y}$ should not include fossil fuels co-fired in the boiler(s) but should include all other fossil fuel consumption at the project site that is attributable to the project activity, such as for on-site transportation or treatment of biomass residues

Data / Parameter:	$EC_{PJ,y}$
Data unit:	MWh
Description:	On-site electricity consumption attributable to the project activity during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	Use electricity meters. The quantity shall be cross-checked with electricity purchase receipts
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	Cross-check measurement results with invoices for purchased electricity if available
Any comment:	Shall only be monitored if default CF is not applicable.

Data / Parameter:	$EF_{grid,y}$
Data unit:	tCO ₂ /MWh
Description:	CO ₂ emission factor for electricity used from the grid
Source of data:	Use ACM0002 to calculate the grid emission factor. If electricity consumption ($EC_{PJ,y}$) is less than 15 GWh/yr, the average grid emission factor (including all grid-connected power plants) may be used.
Measurement procedures (if any):	
Monitoring frequency:	Either once at the start of the project activity or updated annually, consistent with guidance in ACM0002
QA/QC procedures:	Apply procedures in ACM0002
Any comment:	Shall only be monitored if default CF is not applicable. All data and parameters to determine the grid electricity emission factor, as required by ACM0002, shall be included in the monitoring plan

Data / Parameter:	N_y
Data unit:	-
Description:	Number of truck trips during the year y
Source of data:	On-site measurements
Measurement procedures (if any):	-
Monitoring frequency:	Continuously
QA/QC procedures:	Check consistency of the number of truck trips with the quantity of biomass combusted.
Any comment:	Shall only be monitored if default CF is not applicable. Project participants have to monitor either this parameter or the average truck load TL_y

Data / Parameter:	TL_y
Data unit:	Tons or liter
Description:	Average truck load of the trucks used
Source of data:	On-site measurements
Measurement procedures (if any):	Determined by averaging the weights of each truck carrying biomass to the project plant
Monitoring frequency:	Continuously, aggregated annually
QA/QC procedures:	-
Any comment:	Shall only be monitored if default CF is not applicable. Project participants have to monitor either the number of truck trips N_y or this parameter

Data / Parameter:	AVD_y
Data unit:	Km
Description:	Average return trip distance (from and to) between the biomass fuel supply sites and the site of the project plant during the year y
Source of data:	Records by project participants on the origin of the biomass
Measurement procedures (if any):	
Monitoring frequency:	Regularly
QA/QC procedures:	Check consistency of distance records provided by the truckers by comparing recorded distances with other information from other sources (e.g. maps)
Any comment:	Shall only be monitored if default CF is not applicable. If biomass is supplied from different sites, this parameter should correspond to the mean value of km traveled by trucks that supply the biomass plant

Data / Parameter:	$FC_{TR,i,y}$
Data unit:	Mass or volume unit
Description:	Fuel consumption of fuel type i in trucks for transportation of biomass residues during the year y
Source of data:	Fuel purchase receipts or fuel consumptions meters in the trucks
Measurement procedures (if any):	
Monitoring frequency:	Continuously, aggregated annually
QA/QC procedures:	Cross-checked the resulting CO ₂ emissions for plausibility with a simple calculation based on the distance approach (Option 1)
Any comment:	Shall only be monitored if default CF is not applicable. This parameter only needs to be monitored if Option 2 is chosen to estimate CO ₂ emissions from transportation

Data / Parameter:	NCV_i
Data unit:	GJ/mass or volume unit
Description:	Net calorific value of fossil fuel type i
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default net calorific values (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the values in a conservative manner and justify the choice
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement. In case of other data sources: Review the appropriateness of the data annually
QA/QC procedures:	Check consistency of measurements and local / national data with default values by the IPCC. If the values differ significantly from IPCC default values, collect additional information or conduct additional measurements
Any comment:	

Data / Parameter:	NCV_k
Data unit:	GJ/ton of dry matter or GJ/liter
Description:	Net calorific value of biomass residue type k
Source of data:	Measurements
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards. Measure the NCV based on dry biomass
Monitoring frequency:	At least every six months, taking at least three samples for each measurement
QA/QC procedures:	Check the consistency of the measurements by comparing the measurement results with measurements from previous years, relevant data sources (e.g. values in the literature, values used in the national GHG inventory) and default values by the IPCC. If the measurement results differ significantly from previous measurements or other relevant data sources, conduct additional measurements. Ensure that the NCV is determined on the basis of dry biomass
Any comment:	

Data / Parameter:	$EF_{km,CO_2,y}$
Data unit:	tCO ₂ /km
Description:	Average CO ₂ emission factor per km for the trucks during the year y
Source of data:	Conduct sample measurements of the fuel type, fuel consumption and distance traveled for all truck types. Calculate CO ₂ emissions from fuel consumption by multiplying with appropriate net calorific values and CO ₂ emission factors. For net calorific values and CO ₂ emission factors, use reliable national default values or, if not available, (country-specific) IPCC default values. Alternatively, choose emission factors applicable for the truck types used from the literature in a conservative manner (i.e. the higher end within a plausible range)
Measurement procedures (if any):	
Monitoring frequency:	At least annually
QA/QC procedures:	Cross-check measurement results with emission factors referred to in the literature
Any comment:	Shall only be monitored if default CF is not applicable.

Data / Parameter:	$EF_{CH_4,BF}$
Data unit:	tCH ₄ /GJ
Description:	CH ₄ emission factor for the combustion of the biomass residues in the boilers
Source of data:	On-site measurements or default values, as provided in Table 2
Measurement procedures (if any):	The CH ₄ emission factor may be determined based on a stack gas analysis using calibrated analyzers
Monitoring frequency:	At least quarterly, taking at least three samples per measurement
QA/QC procedures:	Check the consistency of the measurements by comparing the measurement results with measurements from previous years, relevant data sources (e.g. values in the literature, values used in the national GHG inventory) and default values by the IPCC. If the measurement results differ significantly from previous measurements or other relevant data sources, conduct additional measurements
Any comment:	Monitoring of this parameter for project emissions is only required if CH ₄ emissions from biomass combustion are included in the project boundary. Note that a conservative factor shall be applied, as specified in the baseline methodology

Data / Parameter:	$EF_{\text{burning,CH}_4,k,y}$
Data unit:	tCH ₄ /GJ
Description:	CH ₄ emission factor for uncontrolled burning of the biomass residue type k during the year y
Source of data:	Undertake measurements or use referenced and reliable default values (e.g., IPCC)
Measurement procedures (if any):	
Monitoring frequency:	Review of default values: annually Measurements: once at the start of the project activity
QA/QC procedures:	Cross-check the results of any measurements with IPCC default values. If there is a significant difference, check the measurement method and increase the number of measurements in order to verify the results
Any comment:	Monitoring of this parameter for project emissions is only required if CH ₄ emissions from biomass combustion are included in the project boundary. Note that a conservative factor shall be applied, as specified in the baseline methodology

Data / Parameter:	$EF_{\text{CO}_2,LE}$
Data unit:	tCO ₂ /GJ
Description:	CO ₂ emission factor of the most carbon intensive fuel used in the country
Source of data:	Identify the most carbon intensive fuel type from the national communication, other literature sources (e.g. IEA). Possibly consult with the national agency responsible for the national communication/GHG inventory. If available, use national default values for the CO ₂ emission factor. Otherwise, IPCC default values may be used
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	

Data / Parameter:	-
Data unit:	-
Description:	Demonstration that the biomass residue type k from a specific source would continue not to be collected or utilized, e.g. by an assessment whether a market has emerged for that type of biomass residue (if yes, leakage is assumed not be ruled out) or by showing that it would still not be feasible to utilize the biomass residues for any purposes
Source of data:	Information from the site where the biomass is generated
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₁ is used to rule out leakage

Data / Parameter:	-
Data unit:	Tons
Description:	Quantity of biomass residues of type k or m that are utilized (e.g., for energy generation or as feedstock) in the defined geographical region
Source of data:	Surveys or statistics
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₂ is used to rule out leakage or if approach L ₄ is used in combination with approach L ₂ to rule out leakage for the substituted biomass residue type m

Data / Parameter:	-
Data unit:	Tons
Description:	Quantity of available biomass residues of type k or m in the region
Source of data:	Surveys or statistics
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₂ is used to rule out leakage or if approach L ₄ is used in combination with approach L ₂ to rule out leakage for the substituted biomass residue type m

Data / Parameter:	-
Data unit:	
Description:	Availability of a surplus of biomass residue type k or m (which can not be sold or utilized) at the ultimate supplier to the project (or, in case of L ₄ , the former user of the biomass residue type k) and a representative sample of other suppliers in the defined geographical region
Source of data:	Surveys
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₃ is used to rule out leakage or if approach L ₄ is used in combination with approach L ₃ to rule out leakage for the substituted biomass residue type m

Data / Parameter:	$FC_{\text{former user, m, y}}$
Data unit:	Mass or volume unit
Description:	Quantity of fuel type m used by the former user of the biomass residue type n during the year y, where the fuel type m is either (i) a fuel type other than a biomass residue (e.g. fossil fuel or biomass other than biomass residues) or (ii) a biomass residues for which leakage can not be ruled out with approaches L ₂ or L ₃
Source of data:	Former consumer of the biomass residue type k
Measurement procedures (if any):	
Monitoring frequency:	Annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₄ is used to rule out leakage

Data / Parameter:	NCV_m
Data unit:	GJ/ton of dry matter or GJ/liter
Description:	Net calorific value of fuel type m
Source of data:	Either conduct measurements or use accurate and reliable local or national data where available. Where such data is not available, use IPCC default net calorific values (country-specific, if available) if they are deemed to reasonably represent local circumstances. Choose the values in a conservative manner and justify the choice
Measurement procedures (if any):	Measurements shall be carried out at reputed laboratories and according to relevant international standards
Monitoring frequency:	In case of measurements: At least every six months, taking at least three samples for each measurement In case of other data sources: Review the appropriateness of the data annually
QA/QC procedures:	
Any comment:	Monitoring of this parameter is applicable if approach L ₄ is used to rule out leakage

Data / Parameter:	-
Data unit:	MWh
Description:	Electricity generation during the year y at the project site
Source of data:	On-site measurements
Measurement procedures (if any):	
Monitoring frequency:	Annual
QA/QC procedures:	
Any comment:	Monitoring of this parameters is only required if power is generated at the project site. In this case, monitoring is needed to assess whether the applicability condition referring to power generation at the project site is met

IV. REFERENCES AND ANY OTHER INFORMATION

Not applicable.

History of the Document

Version	Date	Nature of revision(s)
01	8.7.2010	Initial adoption